

Model S-HAFT

Automatic Flushing Timer

Flushes Reservoir and Drum Humidifiers Twice Daily



Installation Package includes 15 feet of 3/8" ID tubing, mounting hardware, installation instructions, fittings and tubing clamps for installation on Skuttle units and other manufacturers' humidifiers.

NOTE: In areas where the domestic water supply contains excessive chlorine, use of a chlorine removal filter such as the Skuttle WF-10 Filter is suggested. This will aid in the reduction of corrosion caused by high chlorine content.

Specifications

- Dimensions (See photo, right)

	Water Used per Flush	Water Used per Day
10-Second Flush	16 Ounces	1.5 Gallons
20-Second Flush	32 Ounces	3.0 Gallons
30-Second Flush	48 Ounces	4.5 Gallons

Based on laboratory tests conducted at Skuttle Mfg. Co., completed in August 2005.

Features & Benefits

- Provides flow-thru technology for reservoir- and reservoir-type humidifiers
- Automatically flushes the humidifier water pan with fresh, clean water every two hours
- Programmable to 10-, 20- and 30-second flushes per cycle*
- Reduces or eliminates servicing during the humidification season
- Uses minimal electricity
- Reduces water usage by up to 98 percent when compared to conventional flow-thru humidifiers
- Quick and easy to install—usually less than 20 minutes
- Adaptable to most makes and models of steam- and reservoir-type humidifiers

*Factory setting is for 10-second flushing cycle every two hours

